

BEING A PORTION OF SECTIONS  
20, 21, 22, 30, AND 31, TOWNSHIP  
1 NORTH, RANGE 26 EAST, M.D.M.



- = Set 2" pipe w/concrete plug  
    & Tag RCE 15557 unless  
    otherwise stated.
- ( ) = Per original note 1880 USGLO.
- [ ] = Per MB 5/118-123
- \* = Set or calc. by single  
    Proportionate measure.
- GP = Guard Post (Metal fence post)
- apo = 1930 Topo on file in Bishop  
    Office

Fd. 2" Pipe up 17" M/S 4' in Dia.  
at Base 2' high per MB 5 pg 121  
at N edge of old road per DWP  
Topo Sheet 22-65-504. Set  
conc. plug & Tag RCE 15557 and  
poured conc. around M/S  
SEE DETAIL 30-F

GLO per MB 5/12/1  
Did not search for  
this pipe —

19	20
30	29

\ Fd. M/S 3' at Base 18" high  
 Fd. 2" pipe per M.B. 5/121  
 lying on ground 50'± E'ly.  
 Set 2" pipe up 5" in ctr.  
 of mound concreted  
 w/GP 3' N'ly.

I. N. F.

CN 1/16  
\*Set 2" pipe up 1.0' —  
w/GP 2' 5'y.  
Fd. 2" pipe up 1.0'  
S 3-23-19E 28.00'  
No Ref  
SEE DETAIL 30-C

CITY OF LOS ANGELES

1/4 | 30  
Fd. M/S 2' Dia. —————  
6" high w/ remains  
of old post. Fd bearing  
trees & ditch per  
original notes. Set  
2" pipe up 13" in ctr.  
of mound w/GP 2'S'y  
SEE DETAIL 30-D

C/4 S30  
Set 2" pipe up 19" w/ring of stone 18"  
in Dia. 6" high w/GP 25'ly by intersection.  
Fd 2" pipe up 18" w/ wood  
plug 5" high S10-S3-42W  
26.83' No Ref

1/4 30 | 29  
- Fd. 2" pipe & Not. Forest Service Sign lying on ground. Fd. Bearing Trees per original notes. Set 2" pipe Record Distance from Bearing Trees measured from center at Crown Root. up 2 1/2' in cemented M/S 2' Dia. 12" high w/GP 2' W/ly.

SEE DETAIL 30-E

I. N. F.

1. N. F.

Searched for.  
Not found. —  
Falls in thick  
Aspen Grove

Set 2" pipe up 14"  
w/GP 2' W'ly 25'  
N/o & Dirt Road.

Fd. M/S 3' Dia 6" high  
with 24"x13"x9" Stone per  
original notes. Set 2"  
pipe up 18" w/GP 2'W'y.

Set 2" pipe up 1' in  
M/S 18" in Dia. 6" high  
w/GP 2' N'ly. Pipe  
set 66' N'ly of Gulch  
per original notes.

Note:

-Single proportionate measurement from a half-mile away would make this corner fall only 1.94 ft. northerly and was considered; however, because topo calls in original government notes in this area proved to be extremely verifiable and were recorded to nearest link (See call to ditch at easterly quarter of Section 30 and call to creek between Sections 19 and 24), this corner was assumed to be an existent corner whose position could be identified by acceptable accessories to the original monument position rather than a lost corner or obliterated corner. It was, therefore, set at a record distance of 66.00 ft. North of the center of found gulch, 5 links wide, course South 85° East, per original note and on line between the found corners at the southwest corner of Section 31 and the West quarter corner of Section 30.

3/

1.N.F.

1/4 31 | 32  
Fd M/S 3'x5' 1' high  
w/ 6"x8" fence post  
6' Long lying on  
ground. Set 2" pipe  
up 1' w/GP 2' SW'y.

Fd. 4 1/2' Dia M/S 2' high  
w/4" SQ Post badly decayed  
in ctr. per original notes.  
Set 2" pipe up 18" w/GP 3' N'ly.

✓ Did not search  
for this Point or  
Bearing Tree

~Fd 4' Dia. M/S 18" high  
w/4" Dia Scribed Post  
up 18". A 4" SQ. inscribed  
post per original notes  
is also lying in mound.

31	32
6	5

Vol. 1 of E/D Page 97D